


SURGE PROTECTOR

MODEL

- SPD-20-A280/2P
- SPD-20-A280/4P



- *Pluggable module technology*
- *IEC international standard*
- *Smart protection*
- *Surge suppression*
- *Quick installation*
- *Easy replacement*

IEC 61643-11

Introduction

- A solution for protecting electrical and electronic systems (such as cameras, computers, and PLCs) from high-voltage surges and transient overvoltages caused by lightning strikes or sudden voltage spikes.
- The device operates by diverting excessive surge current safely to ground, helping protect equipment, prevent fire hazards, and improve system safety.

Device Classification


- *Type 1: Installed at the main distribution board to withstand direct lightning surge currents.*
- *Type 2: Installed at sub-distribution panels to protect equipment from transient surges and residual lightning effects.*
- *Type 3: Installed close to sensitive equipment (electronics, telecommunications devices, etc.) to suppress remaining low-level surge voltages.*

Description

- Compact, robust, and aesthetically designed with a plug-in modular structure, compliant with IEC 61643-11 standard.
- Made of high-quality engineering plastic, offering excellent durability, heat resistance, and flame-retardant performance.
- Front status indicator window for easy monitoring (green: normal operation – red: replacement required).
- Helps suppress and limit transient overvoltage surges caused by lightning strikes or electrical switching operations.
- Provides reliable protection for control devices, electrical panels, machinery, and residential or industrial electrical systems.
- Quick DIN rail installation inside electrical panels, allowing easy maintenance and module replacement.

Structure:


- Surge Protection Module (SPD Module):**
 Designed to absorb transient surge voltages caused by lightning or switching operations. Featuring a pluggable and replaceable design, the module can be quickly replaced at the end of its service life without disconnecting wiring from the base.
- Plug-in Base (SPD Base):**
 Mounted directly onto a DIN rail inside the electrical panel, providing secure mechanical support and electrical connection for the SPD module.
 The base includes wiring terminals for 2P (L/N) or 4P (L1, L2, L3, N) configurations, along with a PE grounding terminal located at the bottom.
- Advantages:**
 Quick replacement of damaged or end-of-life SPD modules without removing wiring inside the electrical panel.
 Reduced maintenance time and easier servicing.
 Wiring terminals available for L, N (2P) or L1, L2, L3, N (4P) connections.




Technical Specifications

- Model: SPD-20-A280/2P and SPD-20-A280/4P
- Type: Type 2
- Poles:
 - * 2P (L/N): for single-phase system
 - * 4P (L1/L2/L3/N): for three-phase system
- Max. Continuous Operating Voltage (Uc): 280V AC
- Nominal Discharge Current (In): 20kA
- Maximum Discharge Current (Imax): 40kA
- Protection Voltage Level (Up): $\leq 1.3\text{kV}$
- Frequency: 50/60Hz
- Protection degree: IP20
- Back-up fuse: 63A ~ 100A

Circuit diagram






SPD-20-A280/2P





SPD-20-A280/4P

Wiring diagram



Dimensions



Applications

- Protection for sensitive electronic equipment.
- Residential electrical panels and distribution boards (DB).
- Industrial control panels.
- Electrical systems in factories, offices, and commercial buildings



ILEC ELECTRIC EQUIPMENT CO., LTD

Address: 76 street No. 20, Tan Binh Industrial Park Expansion, Binh Hung Hoa Ward, HCMC.

Tax code: 0313550072 - Tel: (84-28) 37657746

Email: admin@ilec.com.vn - Website: ilec.com.vn - Facebook: ilec.com.vn

